


A		B		C		D		E		F	
RevNo	Revision note	Date		Signature	Checked					RoHS Compliant.	
V1.0	Sketch only	05/06/2025									



Interface Per: MIL-STD-348, IEC 60169-15

Material & Finishing:

- Center condutor: Phosphor bronze, Gold Plating 0.25um over Chemical Nickel
- Insulators: PTFE
- Body : Brass, Nickel Plating 3um
- Crimping Ferrule: Soft Copper,Nickel Plating 3um

Electrical Data:

- Impedance: 50 Ohms
- Frequency: 0~3GHz
- VSWR: ≤1.25
- Dielectric Withstanding voltage:750V Min
- Voltage Rating : 250V Max

Package : 1 PC per bag

Laser Mark: LenoRF

Unless otherwise specified, tolerances as below: .X ±0.15 .xx ±0.1 .xxx ±0.05 Angle: ±2°	Material:	See Notes	Weight	g		
	Finish:	See Notes	Scale	8 : 1		
	Unit	mm	Page	01		
	REV.	V1.0	p/n	01	DWG NO.	3.01.394
Drawn		DATA:	Projection		Cust P/N.	TBD
Checked		DATA:	Title: SMA PLUG FOR RG174 CABLE			
Approved		DATA:				