



A		B		C		D		E		F	
RevNo	Revision note		Date	Signature	Checked	RoHS Compliant.					
V1.0	Sketch only		06/09/2025								



Interface Per: MIL-STD-348, IEC 60169-15

Material & Finishing:

- Center conductor: Phosphor bronze, Gold Plating
- Insulators: PTFE
- Body : Brass, Gold Plating

Electrical Data:

- Impedance: 50 Ohms
- Frequency: 0~6GHz
- VSWR: ≤ 1.05 @ 900MHz,
 ≤ 1.1 @ 1800MHz,
 ≤ 1.2 @ 3000MHz,
 ≤ 1.3 @ 6000MHz,
- Insertion loss: ≤ 0.05 dB @ 900MHz,
 ≤ 0.05 dB @ 1800MHz,
 ≤ 0.05 dB @ 3000MHz,
 ≤ 0.1 dB @ 6000MHz,
- Dielectric Withstanding voltage:1000V Min
- Voltage Rating : 500V Max

Package : 1 PC per bag

Laser Mark: LenoRF

Label Content:

LenoRF
Part No: 3.01.400
Part Name: SMA JACK FLANGE MOUNTING JOINT (4HF)
QTY: 1 PC
Date: WW/YY (Week/year)

Unless otherwise specified, tolerances as below: .x ±0.15 .xx ±0.1 .xxx ±0.05 Angle: ±2°	Material:	See Notes	Weight	g		
	Finish:	See Notes	Scale	8 : 1		
	Unit	mm	Page	01		
	REV.	V1.0	p/n	01	DWG NO.	3.01.400
Drawn	DATA:		Projection		Cust P/N.	TBD
Checked	DATA:		Title: SMA JACK FLANGE MOUNTING JOINT (4HF)			
Approved	DATA:					