

RevNo	Revision note	Date	Signature	Checked
V1.0	Sketch only	06/09/2025		

Interface Per: MIL-STD-348, IEC 60169-15
Cable Type: 086


Material & Finishing:

- Center conductor: Phosphor bronze, Gold Plating
- Insulators: PTFE
- Body : Brass, Gold Plating
- Other Metal Parts: Brass, Gold Plating
- Gasket: Silicone Rubber, Red

Electrical Data:

- Impedance: 50 Ohms
- Frequency: 0~6GHz
- VSWR: ≤1.1 @ 900MHz,
≤1.15 @ 1800MHz,
≤1.2 @ 3000MHz,
≤1.3 @ 6000MHz,
- Insertion loss: ≤0.05dB @ 900MHz,
≤0.05dB @ 1800MHz,
≤0.05dB @ 3000MHz,
≤0.1dB @ 6000MHz,
- Dielectric Withstanding voltage:1000V Min
- Voltage Rating : 500V Max

Package : 1 PC per bag
Laser Mark: LenoRF



Label Content:

LenoRF
Part No: 3.01.401
Part Name: SMA JACK BULKHEAD FOR 086 CABLE
QTY: 1 PC
Date: WW/YY (Week/year)

Unless otherwise specified,
tolerances as below:

.x ±0.15
.xx ±0.1
.xxx ±0.05
Angle: ±2°

Material:	See Notes	Weight	g		
Finish:	See Notes	Scale	8 : 1		
Unit	mm	Page	01		
REV.	V1.0	p/n	01		
Drawn	DATA:	Projection		DWG NO.	3.01.401
Checked	DATA:	Title: SMA JACK BULKHEAD FOR 086 CABLE		Cust P/N.	TBD
Approved	DATA:				