

A		B		C		D	E	F
RevNo	Revision note	Date		Signature	Checked	RoHS Compliant.		
V1.0	Sketch only	26/10/2024						

Interface Per: MIL-STD-348, IEC 60169-16
Cable Type: RG58/RG223/RG142/RG400


Material & Finishing:

- Center conductor: Phosphor bronze, Gold Plating
- Insulators: PTFE
- Body : Brass, Nickel Plating
- Crimping Ferrule: Soft Copper,Nickel Plating

Electrical Data:

- Impedance: 50 Ohms
- Frequency: 0~6GHz
- VSWR: ≤1.15 @ 900MHz,
≤1.2 @ 1800MHz,
≤1.25 @ 3000MHz,
≤1.5 @ 6000MHz,
- Insertion loss: ≤0.05dB @ 900MHz,
≤0.05dB @ 1800MHz,
≤0.05dB @ 3000MHz,
≤0.1dB @ 6GHz,
- Dielectric Withstanding voltage:1000V Min
- Voltage Rating : 500V Max

Package : 1 PC per bag
Laser Mark: LenoRF



Label Content:

LenoRF
Part No: 3.01.255
Part Name: N PLUG FOR RG58/RG223/RG142/RG400 CABLE
QTY: 1 PC
Date: WW/YY (Week/year)

Unless otherwise specified, tolerances as below: .X ±0.15 .xx ±0.1 .xxx ±0.05 Angle: ±2°	Material:	See Notes	Weight	g		
	Finish:	See Notes	Scale	8 : 1		
	Unit	mm	Page	01		
	REV.	V1.0	p/n	01	DWG NO.	3.04.0255
Drawn		DATA:	Projection		Cust P/N.	TBD
Checked		DATA:	Title: N PLUG FOR RG58/RG223/RG142/RG400 CABLE			
Approved		DATA:				