

A		B		C		D		E		F	
RevNo	Revision note	Date		Signature	Checked					RoHS Compliant.	
V1.0	Sketch only	28/06/2024									

Interface Per: MIL-STD-348, IEC 60169-16
Cable Type: RG8


Material & Finishing:

- Center condutor: Phosphor bronze, Gold Plating
- Insulators: PTFE
- Body : Brass, Ternary alloy Plating
- Crimping Ferrule: Soft Copper,Nickel Plating

Electrical Data:

- Impedance: 50 Ohms
- Frequency: 0~6GHz
- VSWR: ≤1.2 @ 900MHz,
≤1.25 @ 1800MHz,
≤1.35 @ 3000MHz,
≤1.6 @ 6000MHz,
- Insertion loss: ≤0.05dB @ 900MHz,
≤0.05dB @ 1800MHz,
≤0.05dB @ 3000MHz,
≤0.1dB @ 6000MHz,
- Dielectric Withstanding voltage:1000V Min
- Voltage Rating : 500V Max

Package : 1 PC per bag
Laser Mark: LenoRF



Label Content:

LenoRF
Part No: 3.04.0273
Part Name: N JACK FOR RG8 CABLE
QTY: 1 PC
Date: WW/YY (Week/year)

Unless otherwise specified, tolerances as below: .x ±0.15 .xx ±0.1 .xxx ±0.05 Angle: ±2°	Material:	See Notes	Weight	g		
	Finish:	See Notes	Scale	8 : 1		
	Unit	mm	Page	01		
	REV.	V1.0	p/n	01		
	Drawn	DATA:	Projection		DWG NO.	3.04.0273
	Checked	DATA:	Title: N JACK FOR RG8 CABLE		Cust P/N.	TBD
	Approved	DATA:				