


A		B		C	
RevNo	Revision note	Date	Signature	Checked	
V1.0	Sketch only	09/01/2025			

RoHS Compliant.



Interface Per: MIL-STD-348, IEC 60169-16

Material & Finishing:

- Center condutor: Phosphor bronze, Gold Plating
- Insulators: PTFE
- Body : Brass, Nickel Plating

Electrical Data:

- Impedance: 50 Ohms
- Frequency: 0~6GHz
- VSWR: ≤ 1.1 @ 900MHz,
 ≤ 1.15 @ 1800MHz,
 ≤ 1.2 @ 3000MHz,
 ≤ 1.35 @ 6000MHz
- Insertion loss: $\leq 0.05\text{dB}$ @ 900MHz,
 $\leq 0.05\text{dB}$ @ 1800MHz,
 $\leq 0.05\text{dB}$ @ 3000MHz,
 $\leq 0.1\text{dB}$ @ 3000MHz,
- Dielectric Withstanding voltage:500V Min
- Voltage Rating : 350V Max

Package : 1 PC per bag

Laser Mark: LenoRF

Label Content:

LenoRF
 Part No: 3.17.011
 Part Name: N RIGHT ANGLE PLUG TO JACK RF ADAPTER
 QTY: 1 PC
 Date: WW/YY (Week/year)

Unless otherwise specified, tolerances as below: .x ±0.15 .xx ±0.1 .xxx ±0.05 Angle: ±2°	Material:	See Notes	Weight	g		
	Finish:	See Notes	Scale	8 : 1		
	Unit	mm	Page	01		
	REV.	V1.0	p/n	01	DWG NO.	3.17.011
Drawn		DATA:	Projection		Cust P/N.	TBD
Checked		DATA:	Title: N RIGHT ANGLE PLUG TO JACK RF ADAPTER			
Approved		DATA:				