


A		B		C	
RevNo	Revision note	Date		Signature	Checked
V1.0	Sketch only	21/01/2025			

RoHS Compliant.



Interface Per: MIL-STD-348,

Material & Finishing:

- Center condutor: Beryllium bronze, Gold Plating
- Insulators: PTFE
- Body : Brass, Ternary alloy Plating

Electrical Data:


- Impedance: 50 Ohms
- Frequency: 0~11GHz
- VSWR: ≤1.05 @ 900MHz,
≤1.1 @ 1800MHz,
≤1.15 @ 3000MHz,
≤1.2 @ 6000MHz
- Insertion loss: ≤0.05dB @ 900MHz,
≤0.05dB @ 1800MHz,
≤0.05dB @ 3000MHz,
≤0.1dB @ 6000MHz,
- Proof Voltage : 500 Veff
- Working voltage: 350 Veff

Package : 1 PC per bag

Laser Mark: LenoRF

Label Content:

LenoRF
 Part No: 3.17.133
 Part Name: N JACK TO SMA JACK ADAPTOR
 QTY: 1 PC
 Date: WW/YY (Week/year)

Unless otherwise specified, tolerances as below: .X ±0.15 .xx ±0.1 .xxx ±0.05 Angle: ±2°	Material:	See Notes	Weight	g		
	Finish:	See Notes	Scale	8 : 1		
	Unit	mm	Page	01		
	REV.	V1.0	p/n	01	DWG NO.	3.17.133
Drawn		DATA:	Projection		Cust P/N.	TBD
Checked		DATA:	Title: N JACK TO SMA JACK ADAPTOR			
Approved		DATA:				